


P-Channel Enhancement Mode MOSFET

Parameter	Value	Unit
V_{DS}	-30	V
$R_{DS(on)}$	10	m Ω
I_D	-12.5	A



SOP-8

Features

- Advanced trench cell design
- Low Thermal Resistance
- Low Gate Charge

Applications

- Motor/Body Load Control
- Load Switch
- DC-DC converters and Off-line UPS

Absolute Maximum Ratings ($T_A=25^{\circ}\text{C}$, unless otherwise noted)

Parameter		Symbol	Value	Unit
Drain-Source Voltage		V_{DS}	-30	V
Gate-Source Voltage		V_{GS}	± 20	V
Continuous Drain Current	$T_C=25^{\circ}\text{C}$	I_D	-12.5	A
	$T_C=70^{\circ}\text{C}$		-8.5	
Pulsed Drain Current ¹		I_{DM}	-44	A
Single Pulse Avalanche Energy ²		E_{AS}	53	mJ
Total Power Dissipation	$T_C=25^{\circ}\text{C}$	P_D	4.8	W
Operating Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	$^{\circ}\text{C}$

Thermal Characteristics

Parameter	Symbol	Typ.	Max.	Unit
Thermal Resistance from Junction to Ambient ¹	$R_{\theta JA}$	---	75	$^{\circ}\text{C/W}$
Thermal Resistance Junction-Ambient ¹ ($t \leq 10\text{s}$)		---	40	$^{\circ}\text{C/W}$
Thermal Resistance Junction-Case ¹	$R_{\theta JC}$	---	24	$^{\circ}\text{C/W}$

Electrical Characteristics($T_J=25^{\circ}\text{C}$, unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V$, $I_D=-250\mu A$	-30	-	-	V
BVDSS Temperature Coefficient	$\Delta BV_{DSS}/\Delta T_J$	Reference to 25°C , $I_D=-1\text{mA}$	-	-	-	$V/^{\circ}\text{C}$
Static Drain-Source On-Resistance ²	$R_{DS(ON)}$	$V_{GS}=-10V$, $I_D=-1A$	-	10	13	m Ω
		$V_{GS}=-4.5V$, $I_D=-1A$	-	15	20	
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS}=V_{DS}$, $I_D=-250\mu A$	-1.0	-	-2.5	V
VGS(th) Temperature Coefficient	$\Delta V_{GS(th)}$		-	-	-	mV/ $^{\circ}\text{C}$
Drain-Source Leakage Current	I_{DSS}	$V_{DS}=-30V$, $V_{GS}=0V$, $T_J=25^{\circ}\text{C}$	-	-	-1	μA
		$V_{DS}=-30V$, $V_{GS}=0V$, $T_J=55^{\circ}\text{C}$	-	-	-5	
Gate-Source Leakage Current	I_{GSS}	$V_{GS}=\pm 20V$, $V_{DS}=0V$	-	-	± 100	nA
Gate Resistance	R_g	$V_{DS}=0V$, $V_{GS}=0V$, $f=1\text{MHz}$	-	-	-	Ω
Total Gate Charge (-4.5V)	Q_g	$V_{DS}=-15V$, $V_{GS}=-4.5V$, $I_D=-5A$	-	26	-	nC
Gate-Source Charge	Q_{gs}		-	1.2	-	
Gate-Drain Charge	Q_{gd}		-	2.4	-	
Turn-On Delay Time	$T_{d(on)}$	$V_{DD}=-15V$, $V_{GS}=-10V$, $R_G=3.3\Omega$, $I_D=-5A$	-	11	-	ns
Rise Time	T_r		-	15	-	
Turn-Off Delay Time	$T_{d(off)}$		-	52	-	
Fall Time	T_f		-	24	-	
Input Capacitance	C_{iss}	$V_{DS}=-15V$, $V_{GS}=0V$, $f=1\text{MHz}$	-	1810	-	pF
Output Capacitance	C_{oss}		-	241	-	
Reverse Transfer Capacitance	C_{rss}		-	213	-	

Diode Characteristics

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Continuous Source Current ^{1,5}	I_S	$V_G=V_D=0V$, Force Current	-	-	-12.5	A
Pulsed Source Current ^{2,5}	I_{SM}		-	-	-44	A
Diode Forward Voltage ²	V_{SD}	$V_{GS}=0V$, $I_S=-1A$, $T_J=25^{\circ}\text{C}$	-	-	-1.2	V

Note :

- 1.The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.
- 2.The data tested by pulsed , pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$
3. The EAS data shows Max. rating . The test condition is $V_{DD}=-25V$, $V_{GS}=-10V$, $L=0.1\text{mH}$, $I_{AS}=-38A$
4. The power dissipation is limited by 150°C junction temperature
5. The data is theoretically the same as I_D and I_{DM} , in real applications , should be limited by total power dissipation.

Typical Characteristics




Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. Forward Characteristics of Reverse




Figure 4. $R_{DS(on)}$ vs. V_{GS}




Figure 5. $R_{DS(on)}$ vs. I_D




Figure 6. Normalized $R_{DS(on)}$ vs. Temperature




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9. Power Dissipation




Figure 10. Safe Operating Area





Figure 11. Normalized Maximum Transient Thermal Impedance

Package Outlines Dimensions (Units: mm)

SOP-8



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270(BSC)		0.050(BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

***Important Usage Information and Disclaimer**

The specifications of Zhuhai Hypersemi Co., Ltd. products are not guarantees of product characteristics. They reflect typical performance expected in standard applications, which may vary with specific uses. Users must conduct prior testing for their applications and make necessary adjustments.

Users are responsible for the safety of applications utilizing our products and must implement adequate safety measures to prevent physical injury, fire, or other risks in case of product failure. It is the user's duty to ensure that application designs comply with all applicable laws and standards. Our products must not be used in any applications where a product failure could reasonably result in personal injury, unless specifically authorized in a signed document by Zhuhai Hypersemi Co., Ltd.

No representations or warranties are made regarding the accuracy or completeness of this information, including any claims of non-infringement of third-party intellectual property rights. Zhuhai Hypersemi Co., Ltd. assumes no liability for any applications or uses of its products and does not grant any licenses to its intellectual property rights or those of others. We also make no claims regarding non-infringement of third-party intellectual property rights that may arise from applications.

Due to technical requirements, our products may contain hazardous substances. For details, please contact your nearest sales office. This document replaces all previous information and may be updated. We reserve the right to make changes.