


### 34mm Half Bridge SiC Module

Parameter	Value	Unit
$V_{DS}$	1700	V
$I_D$	300	A
$R_{DS(ON)}$	8.7	m $\Omega$
$Q_G$	504	nC



#### Features:

- High Current Density
- Low Inductive Design
- Low Switching Losses
- High-frequency Operation
- Zero Turn-off Tail Current from MOSFET

#### Applications:

- High Power Converters
- Motor Drives
- UPS Systems

#### Absolute Maximum Ratings ( $T_C=25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Value	Unit
$V_{DS}$	Drain-source Voltage	1700	V
$V_{GS}$	Gate-source Voltage	-10/+22	V
$I_D$	Drain Current (continuous) ( $T_C=25^\circ\text{C}$ )	300	A
$I_{DM}$	Drain Current (pulsed)	600	A
$T_{op}; T_{stg}$	Operating and Storage Temperature Range	-40 to +150	$^\circ\text{C}$
$T_J$	Junction Temperature	175	$^\circ\text{C}$
$R_{th(j-c)}$	Thermal Resistance, Junction-to- heat sink	0.14	$^\circ\text{C}/\text{W}$

#### MOSFET Characteristics

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
Static characteristics (at $T_C=25^\circ\text{C}$ unless otherwise specified)						
$B_{VDS}$	Drain-source Breakdown Voltage	1700	-	-	V	$V_{GS}=0\text{V}$
$I_{DSS}$	Zero Gate Voltage Drain Current	-	-	150	$\mu\text{A}$	$V_{DS}=1700\text{V}; V_{GS}=0\text{V}$
$I_{GSS}$	Gate-body Leakage Current	-	-	1.5	$\mu\text{A}$	$V_{GS}=20\text{V}; V_{DS}=0\text{V}$
$V_{GS(th)}$	Gate Threshold Voltage	2.0	-	4.0	V	$V_{DS}=V_{GS}; I_D=30\text{mA}$
$R_{DS(on)}$	Static Drain-source on Resistance	-	8.7	11	m $\Omega$	$V_{GS}=18\text{V}; I_D=150\text{A}; T_J=25^\circ\text{C}$
$V_{GS(on)}$	Recommended Turn-on Voltage	-	18	-	V	Static
$V_{GS(off)}$	Recommended Turn-off Voltage	-	-5	-	V	
$R_G$	Gate Resistance	-	1.2	-	$\Omega$	$V_{GS}=0\text{V}; f=1\text{MHz}$
Dynamic characteristics (at $T_C=25^\circ\text{C}$ unless otherwise specified)						

$C_{iss}$	Input Capacitance	-	19.4	-	nF	$V_{DS}=1200V$ ; $f=1MHz$ ; $V_{AC}=25mV$
$C_{oss}$	Output Capacitance	-	0.59	-		
$C_{rSS}$	Reverse Transfer Capacitance	-	48	-	pF	
$E_{on}$	Turn-on Switching Energy	-	14.1	-	mJ	$V_{DD}=1200V$ ; $V_{GS}=-5/+18V$ $I_D=150A$ ; $R_{G(ext)}=5\Omega$ Load=100 $\mu$ H
$E_{off}$	Turn-off Switching Energy	-	8.1	-		
$Q_{GS}$	Gate-Source Charge	-	156	-	nC	$V_{DD}=1200V$ ; $V_{GS}=-5/+18V$ $I_D=150A$
$Q_{GD}$	Gate-drain Charge	-	150	-		
$Q_G$	Total Gate Charge	-	504	-		
$t_{d(on)}$	Turn-on Delay Time	-	106	-	ns	$V_{DD}=1200V$ ; $V_{GS}=-5/+18V$ $I_D=150A$ ; $R_{G(ext)}=5\Omega$ Load=100 $\mu$ H
$t_r$	Rise Time	-	48	-		
$t_{d(off)}$	Turn-off Delay Time	-	241	-		
$t_f$	Fall Time	-	69	-		


**Body Diode Characteristics** ( $T_J=25^\circ C$  unless otherwise specified)

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
$V_{FSD}$	Forward Voltage	-	-	6	V	$V_{GS}=0V$ ; $I_F=150A$
$I_S$	Continuous Diode Forward Current	-	150	-	A	$V_{GS}=0V$ ; $T_C=25^\circ C$
$T_{RR}$	Reverse Recovery Time	-	42	-	ns	$V_{GS}=-5/+18V$ ; $I_F=150A$ $V_R=1200V$
$Q_{RR}$	Reverse Recovery Charge	-	2754	-	nC	
$I_{RRM}$	Peak Reverse Recovery Current	-	74	-	A	


**Module Physical Characteristics**

Symbol	Parameter	Min.	Typ.	Max.	Unit	Test Conditions
$V_{ISOL}$	Isolation Test Voltage	-	3.0	-	kV	$f=50Hz$ ; $t=1min$
$L_{Stray}$	Stray Inductance	-	30	-	nH	
W	Weight	-	160	-	g	
M	Mounting Torque	2.5	-	5.0	N·m	M5


**Typical Characteristics**




**Figure 1**  
 Output Characteristics ( $T_J=25\text{ }^\circ\text{C}$ )




**Figure 2**  
 Normalized on-resistance vs. Temperature




**Figure 3**  
 Threshold Voltage vs. Temperature




**Figure 4**  
 Transfer Characteristic for Various  $T_J$




**Figure 5**  
 Diode Characteristic at 25 °C




**Figure 6**  
 Typical Gate Charge Characteristics




**Figure 7**  
 Typical Capacitances vs. Drain-source Voltage



**Figure 8**  
 Inductive Switching Energy vs. Drain Current




**Figure 9**  
 Switching Time Description




**Figure 10**  
 Safe Operating Area

**Circuit Diagram**



**Package Outlines(Unit: mm):**



**\*Important Usage Information and Disclaimer**

The specifications of Zhuhai Hypersemi Co., Ltd. products are not guarantees of product characteristics. They reflect typical performance expected in standard applications, which may vary with specific uses. Users must conduct prior testing for their applications and make necessary adjustments.

Users are responsible for the safety of applications utilizing our products and must implement adequate safety measures to prevent physical injury, fire, or other risks in case of product failure. It is the user's duty to ensure that application designs comply with all applicable laws and standards. Our products must not be used in any applications where a product failure could reasonably result in personal injury, unless specifically authorized in a signed document by Zhuhai Hypersemi Co., Ltd.

No representations or warranties are made regarding the accuracy or completeness of this information, including any claims of non-infringement of third-party intellectual property rights. Zhuhai Hypersemi Co., Ltd. assumes no liability for any applications or uses of its products and does not grant any licenses to its intellectual property rights or those of others. We also make no claims regarding non-infringement of third-party intellectual property rights that may arise from applications.

Due to technical requirements, our products may contain hazardous substances. For details, please contact your nearest sales office. This document replaces all previous information and may be updated. We reserve the right to make changes.