


Silicon Carbide Power MOSFET

Parameter	Value	Unit
V_{DS}	650	V
I_D	11	A
$R_{DS(ON)}$	380	m Ω
Q_G	21.3	nC



PDFN5x6

Features

- High Blocking Voltage with Low On-Resistance
- High Speed Switching with Low Capacitances
- Avalanche Ruggedness
- Easy to Parallel and Simple to Drive

Applications

- Battery Chargers
- Motor Drives
- Pulsed Power Applications
- High Voltage DC/DC Converters
- Switched-Mode Power Supply(SMPS)

Absolute Maximum Ratings (at $T_J=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-source Voltage	V_{DS}	650	V
Gate-source Voltage (Absolute maximum values)	V_{GS}	-10/+22	V
Gate-source Voltage (Recommended operational values)		0/+18	
Drain Current (continuous; $T_C=25^\circ\text{C}$); $V_{GS}=15\text{V}$	I_D	1	A
Drain Current (continuous; $T_C=100^\circ\text{C}$); $V_{GS}=15\text{V}$		9	
Drain Current (pulsed); $V_{GS}=15\text{V}$; $T_C=25^\circ\text{C}$	I_{DM}	22	A
Power Dissipation ($T_C=25^\circ\text{C}$, $T_J=175^\circ\text{C}$)	P_D	52	W
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to +175	$^\circ\text{C}$
Thermal Resistance from Junction to Case	$R_{\theta JC}$	2.88	$^\circ\text{C/W}$

Electrical Characteristics

Parameter	Symbol	Conditions	Value			Unit
			Min.	Typ.	Max.	
Static characteristics (at $T_C=25^\circ\text{C}$ unless otherwise specified)						
Drain-Source Breakdown Voltage	$B_{V_{DS}}$	$V_{GS}=0\text{V}; I_D=500\mu\text{A}$	650	-	-	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=650\text{V}; V_{GS}=0\text{V}$	-	-	10	μA
Gate-Body Leakage Current	I_{GSS}	$V_{GS}=18\text{V}; V_{DS}=0\text{V}$	-	-	250	nA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS}=V_{DS}; I_{DS}=1.8\text{mA}; T_J=25^\circ\text{C}$	2.7	-	4.5	V
Static Drain-Source on Resistance	$R_{DS(on)}$	$V_{GS}=15\text{V}; I_D=5\text{A}; T_J=25^\circ\text{C}$	-	380	500	m Ω
		$V_{GS}=15\text{V}; I_D=5\text{A}; T_J=175^\circ\text{C}$	-	325	-	
		$V_{GS}=18\text{V}; I_D=5\text{A}; T_J=25^\circ\text{C}$	-	260	-	
		$V_{GS}=18\text{V}; I_D=5\text{A}; T_J=175^\circ\text{C}$	-	270	-	
Dynamic characteristics (at $T_C=25^\circ\text{C}$ unless otherwise specified)						
Input Capacitance	C_{iss}	$V_{DS}=500\text{V}; f=1\text{MHz}; V_{GS}=0\text{V}$ $T_J=25^\circ\text{C}$	-	254	-	pF
Output Capacitance	C_{oss}		-	20.2	-	
Reverse Transfer Capacitance	C_{rss}		-	2.4	-	
Total Gate Charge	Q_G	$V_{DD}=500\text{V}; V_{GS}=0/15\text{V}; I_D=5\text{A}$ $T_J=25^\circ\text{C}$	-	21.3	-	nC
Gate-Source Charge	Q_{GS}		-	6.7	-	
Gate-Drain Charge	Q_{GD}		-	11.5	-	
Internal Gate Resistor	R_{Gint}	$f=1\text{MHz};$	-	6.4	-	Ω
Turn-on Delay Time	$t_{d(on)}$	$V_{DD}=500\text{V}; V_{GS}=0/15\text{V}; I_D=5\text{A};$ $R_{g(ext)}=10\Omega$	-	24	-	ns
Rise Time	t_r		-	42	-	
Turn-off Delay Time	$t_{d(off)}$		-	26.8	-	
Fall Time	t_f		-	76	-	

Reverse SiC Diode Characteristics(at $T_J=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Values			Units
			Min.	Typ.	Max.	
Diode Forward Voltage	V_{FSD}	$V_{GS}=0\text{V}; I_F=3\text{A}; T_J=25^\circ\text{C}$	-	3.5	-	V
Continuous Diode Forward Current	I_S	$V_{GS}=0\text{V}; T_J=25^\circ\text{C}$	-	11	-	A
Reverse Recovery Time	t_{RR}	$V_R=500\text{V}; V_{GS}=0\text{V}; I_F=5\text{A};$ $di/dt=530\text{A}/\mu\text{s}; T_J=25^\circ\text{C}$	-	17.8	-	ns
Reverse Recovery Charge	Q_{RR}		-	33.7	-	nC
Peak Reverse Recovery Current	I_{RRM}		-	3.5	-	A

Typical Characteristics




Fig1. Output Characteristics $T_j=25^{\circ}\text{C}$




Fig2. Output Characteristics $T_j=175^{\circ}\text{C}$




Fig3. Typical Transfer Characteristics




Fig4. Normalized On-Resistance vs. Temperature




Fig5. Normalized On-Resistance vs. Drain Current For Various Temperatures




Fig6. Normalized Threshold Voltage vs. Temperature




Fig7. Capacitances vs. Drain-Source Voltage (0-200V)




Fig8. Capacitances vs. Drain-Source Voltage (0-600V)





Fig9. Body Diode Characteristics

Package Outlines(Unit:mm)

PDFN5x6



Dim.	Min.	Max.
A	4.8	5.2
B	0.25	0.35
C	1	1.2
C1	Typ0.254	
C2	Typ0.254	
D1	3.35	3.81
E	Typ1.27	
E1	3.9	4.18
L	6	6.3
L1	5.7	6
L2	MAX 0.2	
R	Typ 13°	
All Dimensions in millimeter		

***Important Usage Information and Disclaimer**

The specifications of Zhuhai Hypersemi Co., Ltd. products are not guarantees of product characteristics. They reflect typical performance expected in standard applications, which may vary with specific uses. Users must conduct prior testing for their applications and make necessary adjustments.

Users are responsible for the safety of applications utilizing our products and must implement adequate safety measures to prevent physical injury, fire, or other risks in case of product failure. It is the user's duty to ensure that application designs comply with all applicable laws and standards. Our products must not be used in any applications where a product failure could reasonably result in personal injury, unless specifically authorized in a signed document by Zhuhai Hypersemi Co., Ltd.

No representations or warranties are made regarding the accuracy or completeness of this information, including any claims of non-infringement of third-party intellectual property rights. Zhuhai Hypersemi Co., Ltd. assumes no liability for any applications or uses of its products and does not grant any licenses to its intellectual property rights or those of others. We also make no claims regarding non-infringement of third-party intellectual property rights that may arise from applications.

Due to technical requirements, our products may contain hazardous substances. For details, please contact your nearest sales office. This document replaces all previous information and may be updated. We reserve the right to make changes.