



Silicon Carbide Schottky Diode

Parameter	Value	Unit
V _{RRM}	1700	V
I _F	10*	A
Q _C	120*	nC



TO-247-3L

Features

- Zero reverse recovery current
- Zero forward recovery voltage
- Temperature independent switching behavior
- High temperature operation
- High frequency operation

Applications

- Motor drives
- Photovoltaic inverters
- Uninterruptible Power Supply
- High-voltage DC-DC converter

Maximum Ratings (at T_J=25°C unless otherwise specified)

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	V _{RRM}	1700	V
Surge Peak Reverse Voltage	V _{RSM}	1700	V
Continuous Forward Current T _C =25°C T _C =135°C T _C =165.5°C	I _F	48.4* 23.5* 10*	A
Repetitive Peak Forward Surge Current T _C = 25°C, tp=10ms, Half Sine Pulse ,D=0.1, 1000Cycle	I _{FRM}	75*	A
Non-Repetitive Forward Surge Current T _C = 25°C, tp=10ms, Half Sine Pulse	I _{FSM}	150*	A
Non-Repetitive Forward Surge Current T _C = 25°C, tp=10ms, Half Sine Pulse	∫i ² dt	112.5*	A ² s
Power dissipation T _C = 25°C T _C = 110°C	P _{tot}	300* 130*	W
Operating junction Range	T _J	-55 to +175	°C
Storage temperature Range	T _{stg}	-55 to +175	°C

* Per leg; **Per device

Thermal Characteristics

Parameter	Symbol	Typ.	Unit
Thermal resistance, junction – case.	R_{thJC}	0.5* 0.25**	°C/W

Electrical Characteristics(at $T_j=25^{\circ}\text{C}$ unless otherwise specified)

Parameter	Symbol	Test conditions	Value			Unit
			Min.	Typ.	Max.	
DC blocking voltage	V_{DC}		1700			V
Diode forward voltage	V_F	$I_F=10\text{A}, T_j=25^{\circ}\text{C}$ $I_F=10\text{A}, T_j=175^{\circ}\text{C}$		1.36 1.89	1.7 2.5	V
Reverse current	I_R	$V_R=1700\text{V}, T_j=25^{\circ}\text{C}$ $V_R=1700\text{V}, T_j=175^{\circ}\text{C}$		0.35 2.76	50 100	μA
Total capacitive charge	Q_C	$V_R=1200\text{V}, T_j=25^{\circ}\text{C}$		120		nC
Total capacitance	C	$T_j=25^{\circ}\text{C}$ $V_R=0\text{V}, f=1\text{MHz}$ $V_R=400\text{V}, f=1\text{MHz}$ $V_R=800\text{V}, f=1\text{MHz}$		1400 94 68		pF
Capacitance Stored Energy	E_C	$V_R=1200\text{V}$		91		μJ

* Per leg **Per device

Typical Characteristics




Figure 1. Forward Characteristics




Figure 2. Reverse Characteristics




Figure 3. Power Derating




Figure 4. Current Derating
Valid for switching of above 20kHz,
excluding D.C. curve




Figure 5. Capacitance vs. Reverse Voltage




Figure 6. Reverse Charge vs. Reverse Voltage




Figure 7. Capacitance Stored Energy





Figure 8. Transient Thermal Impedance

Package Outlines(Unit:mm)

TO-247-3L



*Important Usage Information and Disclaimer

The specifications of Zhuhai Hypersemi Co., Ltd. products are not guarantees of product characteristics. They reflect typical performance expected in standard applications, which may vary with specific uses. Users must conduct prior testing for their applications and make necessary adjustments.

Users are responsible for the safety of applications utilizing our products and must implement adequate safety measures to prevent physical injury, fire, or other risks in case of product failure. It is the user's duty to ensure that application designs comply with all applicable laws and standards. Our products must not be used in any applications where a product failure could reasonably result in personal injury, unless specifically authorized in a signed document by Zhuhai Hypersemi Co., Ltd.

No representations or warranties are made regarding the accuracy or completeness of this information, including any claims of non-infringement of third-party intellectual property rights. Zhuhai Hypersemi Co., Ltd. assumes no liability for any applications or uses of its products and does not grant any licenses to its intellectual property rights or those of others. We also make no claims regarding non-infringement of third-party intellectual property rights that may arise from applications.

Due to technical requirements, our products may contain hazardous substances. For details, please contact your nearest sales office. This document replaces all previous information and may be updated. We reserve the right to make changes.